

# **ATMOS41 Weather Station**

**Quick Start Guide** 



### **Getting Started**


- Open the INCYT App and register the sensor. When instructed, scan the QR code on the box
- 2 Add the appropriate
  Application within the INCYT
  App, and link the sensor



### **Preparation**

- 3 Unpack the contents and check the component list in the box to ensure that the kit is complete.
- Prepare installation equipment including a 13mm (1/2") spanner, a 42-48mm
  O.D. galvanised mounting pole, and the equipment required to install the pole.
  Concreting the pole into a hole at least 200mm in diameter and 600mm deep is strongly recommended.

### **Product Overview**



- 1 ATMOS 41 Weather Station
- 2 V-bolt with nuts
- 3 Bird Spikes
- 5 This sensor requires a Blue Node, Power Junction and a power source such as a Solar Kit or Power Supply to function, which are available for purchase from incyt.com.au

## **Installation and Mounting**

- 6 When selecting an installation location, ensure that it is clear of obstructions and objects that may interfere with rainfall collection and wind direction readings, such as trees or buildings. Avoid installing more than 2m above from the ground.
- 7 Fabricating a bracket as pictured in Figure 1.1 to distance the Blue Node from the mounting pole is recommended to improve signal strength. When installing the pole, ensure the bracket points towards the Base Station. Mount the assembled weather station to the top of the pole. Tighten the V-bolt nuts by hand until hand-tight, and then tighten with a spanner. Caution: Do not over tighten nuts

8 Concrete the mounting pole into the hole, ensuring it is **sturdy**. Ensure the pole is **level** by using the spirit level located beneath the weather station.

Accuracy of the weather station will be reduced if not mounted completely level on a sturdy pole. If the area is excessively windy, consider shortening the pole height to reduce shaking or swaying of the weather station.

- Orient the weather station with the engraved 'N' on the instrument pointed towards True North. True North can be found using a GPS device or compass.
- Install the Blue Node to the end of the bracket as pictured in Figure 1.1 according to it's Quick Start Guide.
- Install the Power Junction and Power
  Supply as per their Quick Start Guides. First
  connect the Weather Station and Power
  Source to the Power Juction. Then connect
  the Power Juction to the Blue Node.
- 12 Attach bird spikes to the rim of the rain collector, and ensure data is correctly reporting on the App before leaving.



Protect cables from animals by installing sheathing from your local hardware store



Fence off the weather station to protect from damage by animals.

